

Datasheet

1.8" SATA SSD

3MG2-P series

- SATA III solution for industrial field
- High IOPS
- Intelligent error recovery system
- iSMART disk health monitoring
- iData Guard for abnormal power failure



Introduction

Innodisk 1.8" SATA SSD 3MG2-P is SATA III 6Gb/s flash based disk, which delivers excellent performance, especially in random data transfer rate, and which offers reliability making it the ideal solution for a variety of applications, including embedded system, industrial computing, and enterprise field. 1.8" SATA SSD 3MG2-P not only performs unmatched performance, but also designed with Innodisk owned technical knowhow to ensure the data integrity and highest levels of reliability.


1.8" SATA SSD

3MG2-P series

Drawing

Contact us for more information about the 1.8" SATA SSD 3MG2-P

Innodisk is a service-driven provider of industrial embedded flash and DRAM storage products and technologies, with a focus on the industrial/embedded, aerospace and defense, and cloud computing industries.



Headquarters (Taiwan)

5F., No.237, Sec. 1, Datong Rd.,
Xizhi Dist., New Taipei City,
Taiwan (R.O.C.)
Tel: +886-2-77033000
Email: sales@innodisk.com

Branch Offices:

USA
usasales@innodisk.com
+1-510-770-9421
Europe
eusales@innodisk.com
+31-40-3045-400
Japan
jpsales@innodisk.com
+81-3-6667-0161
China
sales_cn@innodisk.com
+86-755-21673689
www.innodisk.com

© 2018 Innodisk Corporation.
All right reserved. Specifications
are subject to change without
prior notice.

20180925

Specifications

Interface	SATA III
Flash Type	MLC
Capacity	1TB
Max. Channels	4
Sequential R/W (MB/sec, max.)*	520 / 450
4K Random (QD32) R/W (IOPS)*	75,000/71,000
Max. Power Consumption	3.2 W (5V x 640mA)
Thermal Sensor	✓
External DRAM Buffer	✓
ATA Security	✓
S.M.A.R.T.	✓
Dimension (WxLxH)	54.0 X 78.5 X 5.00 mm
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -55°C ~ +95°C MTBF: 3 million hours
*Performance based on CrystalDiskMark 3.03 with file size 1000MB	

Ordering Information

Operation Temp.	1TB
Standard Grade (0°C ~ +70°C)	DGS18-01TD81BCBQC
Industrial Grade (-40°C ~ +85°C)	DGS18-01TD81BWBQC