


Datasheet

USB EDC Horizontal 2ME series

- Cost-effective MLC
- Excellent data transfer speed
- Wear-leveling supported
- Low power consumption
- Pin pitch 2.54mm/2.00mm



Introduction

The Innodisk USB EDC (Embedded Disk Card) products provide high capacity USB flash memory storage that electrically complies with High-speed USB 2.0 interface & backward compatible with USB 1.1. The device features attractive small form factor and the connectivity over USB2.0 and the NAND flash architecture provide a faster data transmission.

USB EDC Horizontal 2ME series

Drawing

Contact us for more information
about the USB EDC Horizontal 2ME

Innodisk is a service-driven provider of industrial embedded flash and DRAM storage products and technologies, with a focus on the cloud computing, industrial/embedded, and aerospace and defense industries.

Headquarters (Taiwan)






5F., No.237, Sec. 1, Datong Rd.,
Xizhi Dist., New Taipei City,
Taiwan (R.O.C.)
Tel: +886-2-77033000
Email: sales@innodisk.com

Branch Offices:

USA
usasales@innodisk.com
+1-510-770-9421
Europe
eusales@innodisk.com
+31-40-3045-400
Japan
jpsales@innodisk.com
+81-3-6667-0161
China
sales_cn@innodisk.com
+86-755-21673689
www.innodisk.com

© 2018 Innodisk Corporation.
All right reserved. Specifications
are subject to change without
prior notice.

20181119



Specifications

Interface	USB 2.0
Flash Type	MLC
Connector	Standard, 9pin, 2.54mm
	Low profile, 9pin, 2.00mm
Capacity	8GB~128GB
Max. Channels	1
Sequential R/W (MB/sec, max.)	25 / 17
Max. Power Consumption	0.85 W (5V X 170mA)
H/W Write Protect	Optional
S.M.A.R.T.	-
Dimension (WxLxH)	26.6x36.9x9.6mm (Pin Pitch2.54)
	26.6x36.9x6.6mm (Pin Pitch2.00)
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -55°C ~ +95°C MTBF: 3 million hours

Ordering Information

Pin Pitch	2.54mm				
Operation Temp.	8GB	16GB	32GB	64GB	128GB
Standard Grade (0°C ~ +70°C)	DEUH1-08GI72BC1SC	DEUH1-16GI72BC1SC	DEUH1-32GI72BC1SC	DEUH1-64GI72BC1SC	DEUH1-A28I72BC1SC
Industrial Grade (-40°C ~ +85°C)	DEUH1-08GI72BW1SC	DEUH1-16GI72BW1SC	DEUH1-32GI72BW1SC	DEUH1-64GI72BW1SC	DEUH1-A28I72BW1SC
Pin Pitch	2.00mm				
Operation Temp.	8GB	16GB	32GB	64GB	128GB
Standard Grade (0°C ~ +70°C)	DEUH2-08GI72BC1SC	DEUH2-16GI72BC1SC	DEUH2-32GI72BC1SC	DEUH2-64GI72BC1SC	DEUH2-A28I72BC1SC
Industrial Grade (-40°C ~ +85°C)	DEUH2-08GI72BW1SC	DEUH2-16GI72BW1SC	DEUH2-32GI72BW1SC	DEUH2-64GI72BW1SC	DEUH2-A28I72BW1SC

innodisk

www.innodisk.com